



ETC

200-400a Site Board

Features

- Available in 200a to 400a options.
- 24 x fittings for sockets size 16a 1ph through to 63a 3ph.
- Available with interchangeable isolator switches or with an incoming MCCB breaker.

Specifications

Incoming supply	Up to 400a
Frame size (L x W x H)	1400 x 850 x 420 mm
Enclosure size (L x W x H)	860 x 650 x 280 mm
Board enclosure	IP54
Sockets	IP67
Weight	120 Kg (Spec dependent)
Interchangeable Outgoing ways	IP67 sockets 16a 1 phase, 32a 1ph, 63a 1ph, 16a 3ph, 32a 3ph, 63a 3ph
Outgoing protection	MCB type C or D, RCBOs, earth leakage modules

Additional Features

- Lockable door
- Full length lifting pockets
- Full width rear braces
- Power lock, 125a a 3ph or blank plate incomer

Example Configuration

- 200a incoming isolator switch.
- 2 x 16a 1ph IP67 sockets protected by 2 x 16a 1ph RCBOs.
- 8 x 32a 1ph IP67 sockets protected by 8 x 32a 1ph RCBOs.
- 2 x 63a 1ph IP67 sockets protected by 2 x 63a 1ph MCBs 2 x earth leakage modules.

