



Silenced Generator

100kVA

ENGINE Ref: IVECO / PERKINS

ALTERNATOR Ref: MECC ALTE

Temporary power compliant with the latest NRMM Legislation

- Hot dip galvanised sound attenuated enclosure
- 66 dBA @ 7 meters
- Powder coated standard white
- Bunded 185 litre base fuel tank complete with 3 way valve
- Central lift point and forklift pockets complete with robber bumpers
- 4 pole circuit breaker with earth leakage protection
- Plastic coated locks/handles
- lockable canopy with single common key
- Hardwire via copper bus bars
- Governor - mechanical
- Micro switch protection mounted under perspex
- Ct for genset paralleling
- External contact for autostart
- Mecc alte alternator
- Sump oil vac pump
- Water separator fuel filter
- Hard wire battery isolator
- Socket kit – 1 x 125amp 3 phase
- Oil pressure & water temperature sensor
- Motorised MCCB
- Velcb with on/off switch

| Standby (kVA) | Prime Power (kVA) | Cylinders | Aspiration | Cm3 | kWm @ 1500 rpm | Tank Capacity (Litre) | Fuel Consumption per hour (Litre) | | | dBA @ 7m | Size (mm) (L x H x W) | Wet Weight (kg) | Control Panel |
|---------------|-------------------|-----------|------------|------|----------------|-----------------------|-----------------------------------|-------|-------|----------|--------------------------------|-----------------|------------------|
| | | | | | | | 50% | 75% | 100% | | | | |
| 110 | 100 | 4 | Turbo | 4500 | 87 | 185 Bunded | 11.40 | 17.10 | 22.80 | 66 | 2580 x 1130 x 1640 (L x H x W) | 1835 | DSE 7310 or 8610 |

