



Silenced Generator

160kVA-2022

ENGINE Ref: IVECO

ALTERNATOR Ref: MECC ALTE

Temporary power compliant with the latest NRMM Legislation

- Hot dip galvanised sound attenuated enclosure
- 66 dBA @ 7 meter
- Powder coated standard white
- Bunded 185 litre base fuel tank complete with 3 way valve
- Central lift point and forklift pockets
- Complete with bumpers
- 4 pole circuit breaker with earth leakage protection
- Plastic coated locks/handles
- Lockable canopy with single common key
- Hardwire via copper bus bars
- Governor - mechanical
- MECC alte alternator
- Sump oil vac pump
- Water separator fuel filter
- Micro switch protection mounted under perspex
- Ct for genset paralleling
- External contact for autostart
- Battery isolator
- Socket kit – 1 x 125amp 3 phase
- Oil pressure & water temperature sensor
- Motorised MCCB
- Velcb with on/off switchJohn

Standby (kVA)	Prime Power (kVA)	Engine Make Type	Cylinders	Aspiration	Cm3	kWm @ 1500 rpm	Tank Capacity (Litre)	Fuel Consumption per hour (Litre)			dBA @ 7m	Size (mm) (L x H x W)	Wet Weight (kg)	Control Panel
								50%	75%	100%				
165	150	IVECO	6	Turbo	6700	138	270 Bunded	19.75	26.07	39.50	68	3380 x 1850 x 1130 (L x H x W)	2630	DSE 8610

