



# Silenced Generator

## 160kVA

ENGINE Ref: IVECO / PERKINS

ALTERNATOR Ref: MECC ALTE

### Temporary power compliant with the latest NRMM Legislation

- Hot dip galvanised sound attenuated enclosure
- 66 dBA @ 7 meters
- Powder coated standard white
- Bunded 185 litre base fuel tank complete with 3 way valve
- Central lift point and forklift pockets complete with robber bumpers
- 4 pole circuit breaker with earth leakage protection
- Plastic coated locks/handles
- lockable canopy with single common key
- Hardwire via copper bus bars
- Governor - mechanical
- Micro switch protection mounted under perspex
- Ct for genset paralleling
- External contact for autostart
- Mecc alte alternator
- Sump oil vac pump
- Water separator fuel filter
- Hard wire battery isolator
- Socket kit – 1 x 125amp 3 phase
- Oil pressure & water temperature sensor
- Motorised MCCB
- Velcb with on/off switch

Standby (kVA)	Prime Power (kVA)	Cylinders	Aspiration	Cm3	kWm @ 1500 rpm	Tank Capacity (Litre)	Fuel Consumption per hour (Litre)			dBA @ 7m	Size (mm) (L x H x W)	Wet Weight (kg)	Control Panel
							50%	75%	100%				
110	100	4	Turbo	4500	87	185 Bunded	11.40	17.10	22.80	66	2580 x 1130 x 1640 (L x H x W)	1835	DSE 7310 or 8610

