



Silenced Generator 200kVA-2022

ENGINE Ref: IVECO / CUMMINS

ALTERNATOR Ref: MECC ALTE

Temporary power compliant with the latest NRMM Legislation

- Hot dip galvanised sound attenuated enclosure
- Average 68 dBA @ 7 meters
- Powder coated grey raal 7035
- Bunded 270 litre base fuel tank complete with 3 way valve
- Central lift point and forklift pockets complete with rubber bumpers
- 4 pole circuit breaker with earth leakage protection
- Hardwire via copper bus bars
- Micro switch protection mounted under perspex
- CT for genset paralleling
- Racor filter
- Deep sea 8610 loadshare control panel
- Plastic coated locks/handles
- Lockable canopy with single common key
- IVECO water separator filter
- Sump oil vac pump
- Battery isolator
- Socket kit – 1 x 125amp 3 phase
- Oil pressure & water temperature sensor
- Motorised MCCB
- Velcb with on/off switch
- External contact for autostartJohn F HuntPOWER

Standby (kVA)	Prime Power (kVA)	Engine Make Type	Governor	Tank Capacity (Litre)	Fuel Consumption per hour (Litre)			dBA @ 7m	Size (mm) (L x H x W)	Wet Weight (kg)	Control Panel
					50%	75%	100%				
220	200	IVECO/ CUMMINS	Electronic	270 Bunded	21.55	32.33	43.10	68	3380 x 1850 x 1130	2690	Deep Sea 8610 Loadshare

