



Silenced Generator 20kVA

ENGINE Ref: PERKINS

ALTERNATOR Ref: LEROY SOMER

Temporary power compliant with the latest NRMM Legislation

- Hot dip galvanised sound attenuated enclosure
- Average 65 dBA @7 meters
- Powder coated RAL 7035 white
- Forklift pockets - complete with rubber bumpers
- 4 pole circuit breaker with earth leakage protection
- Bunded 70 litre base fuel tank complete with 3 way valve
- Central lift point
- Low oil pressure shutdown
- Racor filter
- Battery isolator
- Deep Sea 7310 auto control panel
- Plastic coated locks and handles
- Lockable canopy with common single key
- PERKINS water separator filter
- Sump oil vac pump
- High water temperature shutdown
- Socket kit: 2 x 32 AMP SINGLE PHASE AND 1 x 32 AMP 3 pahse

Standby (kVA)	Prime Power (kVA)	Engine Make / Type	Governor	Tank Capacity (Litre)	Fuel Consumption per hour (Litre)			dBA @ 7m	Size (mm) (L x H x W)	Wet Weight (kg)	Control Panel
					50%	75%	100%				
200	20	PERKINS	Mechanical	75	2.70	4.05	5.40	65	5000 x 2400 x 2100 (L x H x W)	700	Deep Sea 7310 Autostart

