



# Silenced Generator

## 40kVA

ENGINE Ref: IVECO / KOHLER

ALTERNATOR Ref: MECC ALTE

### Temporary power compliant with the latest NRMM Legislation

- Engine Make / Type Hot dip galvanised sound attenuated enclosure
- Average 65 dBA @7 meters
- Powder coated RAL 7035 white
- Forklift pockets - complete with rubber bumpers
- 4 pole circuit breaker with variable earth leakage protection
- Bunded 185 litre base fuel tank complete with 3 way valve
- Central lift point
- Low oil pressure shut-down
- TS 26 S002 protection
- External contact auto-start
- Non-motorised MCCB
- Battery isolator
- Deep Sea 7310 auto control panel
- Plastic coated locks and handles
- Lockable canopy with common single key
- IVECO water separator filter
- Sump oil vac pump
- Hard-wire with clamp
- Micro switch protection on bus-bar
- High coolant temperature shut-down
- Fully bunded base-frame with oil and water collection tank
- Oil extraction pump
- Racor filter
- Socket kit: 1 x 63 AMP 3 PHASE & 2 x 32 AMP single phase

Standby (kVA)	Prime Power (kVA)	Engine Make / Type	Governor	Tank Capacity (Litre)	Fuel Consumption per hour (Litre)			dBA @ 7m	Size (mm) (L x H x W)	Wet Weight (kg)	Control Panel
					50%	75%	100%				
45	40	IVECO / KOHLER	Mechanical	185	5.95	8.92	11.90	67	2300 x 1130 x 1580	1285	Deep Sea 7310 Autostart

