



Silenced Generator

500kVA

ENGINE Ref: PERKINS / VOLVO

ALTERNATOR Ref: MECC ALTE

Temporary power compliant with the latest NRMM Legislation

- Hot dip galvanised sound attenuated enclosure
- Average 69 dBA @ 7 metres
- Powder coated grey raal 7035
- Forklift pockets – complete with rubber bumpers
- Deep sea 8610 loadshare synch control panel
- Battery isolator
- 1000 ltr bunded base fuel tank complete with 3 way valve
- CT for genset paralleling
- Battery charger
- Motorised MCCB
- Plastic coated locks and handles
- Lockable canopy with common single key
- Perkins water separator filter
- Sump oil vac pump
- Oil pressure sensor
- Water temperature sensor
- Central lift point lift
- Velcb with on off switch
- Hardwire via copper busbar
- Microswitch protection mounted under perspex
- External contact for autostart John

Standby (kVA)	Prime Power (kVA)	Engine Make Type	Governor	Tank Capacity (Litre)	Fuel Consumption per hour (Litre)			dBA @ 7m	Size (mm) (L x H x W)	Wet Weight (kg)	Control Panel
					50%	75%	100%				
550	500	PERKINS / VOLVO	Electronic	1000	53.05	70.03	106.60	68	4850 x 2300 x 2000	6792	Deep Sea 8610 Loadshare

