



# Silenced Generator 60kVA

ENGINE Ref: IVECO

ALTERNATOR Ref: MECC ALTE

## Temporary power compliant with the latest NRMM Legislation

- Hot dip galvanised sound attenuated enclosure
- Average 67 dBA @7 meters
- Powder coated RAL 7035 white
- Bunded 185 litre base fuel tank complete with 3 way valve
- Central lift point
- Forklift pockets - complete with rubber bumper protection
- 4 pole circuit breaker with variable earth leakage protection
- Hardwire via copper bus bars
- Micro switch protection
- Deep Sea 7310 auto control panel
- TS 26 S002 protection
- Hard-wire with clamp
- Plastic coated locks and handles
- Lockable canopy with common single key
- IVECO water separator filter
- Sump oil vac pump
- Battery isolator
- Socket kit: 1 x 63 AMP 3 PHASE & 2 x 32 AMP single phase
- Low oil pressure shut-down
- High coolant temperature shut-down
- Fully bunded base-frame with oil and water collection tank
- External contact auto-start
- Non motorised MCCB
- Racor filterJohn

Standby (kVA)	Prime Power (kVA)	Engine Make / Type	Governor	Tank Capacity (Litre)	Fuel Consumption per hour (Litre)			dBA @ 7m	Size (mm) (L x H x W)	Wet Weight (kg)	Control Panel
					50%	75%	100%				
66	60	IVECO	Mechanical	185	7.28	10.92	14.56	67	2300 x 1130 x 1700 (L x H x W)	1385	Deep Sea 7310 Autostart

