



# Silenced Generator 800kVA

ENGINE Ref: CUMMINS

‡ALTERNATOR Ref: MECC ALTE

## Temporary power compliant with the latest NRMM Legislation

- Hot dip galvanised sound attenuated enclosure
- Average 70 dBA @ 7 metres
- Powder coated grey raal 7035
- Forklift pockets complete with rubber bumpers
- 4 pole circuit breaker with variable earth leakage protection and on/off switch
- Deep sea 8610 loadshare synch control panel
- Battery isolator
- 1300 litre bunded base fuel tank with 3 way valve
- CT for genset paralleling
- Battery charger
- Plastic coated locks and handles
- Lockable canopy with common single key
- Cummins water separator filter
- Sump oil vac pump
- Oil pressure sensor
- Water temperature sensor
- Central lift point
- Hardwire via copper busbar
- Microswitch protection
- Motorised MCCB
- Racor filterJohn

Standby (kVA)	Prime Power (kVA)	Engine Make Type	Governor	Tank Capacity (Litre)	Fuel Consumption per hour (Litre)			dBa @ 7m	Size (mm)	Wet Weight (kg)	Control Panel
					50%	75%	100%				
880	800	CUMMINS	Electronic	1300	85	121	161	75	5550 × 2300 × 2200 (L × H × W)	10482	Deep Sea 8610 Loadshare

