



Stage V Generator 160kVA-2023

ENGINE Ref: Kohler

ALTERNATOR Ref: Leroy Sommer

Temporary power compliant with the latest NRMM Legislation

- Fully compliant STAGE V engine
- Ultra-silent compact canopy for extra noise suppression
- Full Synchronisation Capability
- Patented Vsi technology
- Hot dip galvanized enclosure
- Powder coated
- Forklift pockets - complete with rubber bumper protection
- 4 Pole circuit breaker with earth leakage protection
- 150 litre bunded fuel tank complete with 3 way valve
- Emergency stop button
- 50/60 Hz Switchable
- Low water/Low oil level alarms
- Battery isolator
- Deep sea control panel 8610 MKii
- Lockable canopy for extra security
- RACOR water separator filter
- Copper busbar with microswitch protection over hardwire door
- Motorised MCCB
- Central lift point
- Socket kit : 1 x 125a 3ph
- Complete with REMOTE FLEET MONITORING option via DSE Webnet
- Internal 400 Litre Adblue Tank

Standby (kVA)	Continuous Power (kVA)	Tank Capacity (Litres)	Fuel Consumption per hour (Litres) 70%	dBA @ 7m	Size (mm) (L x H x W)	Dry Weight (kg)	Control Panel	Socket Kit
160	150	150	22.2	55	3900 x 1130 x 2300 (L x H x W)	3400	Deep Sea 8610 MKii	1 x 25a 3ph

